



HOLLISTER-WHITNEY ELEVATOR CORPORATION

#1 Hollister-Whitney Parkway
 Quincy, IL 62305
 Phone: 217-222-0466

Fax: 217-222-0493
 email: engineering@hollisterwhitney.com
 www. hollisterwhitney.com

HOLLISTER-WHITNEY VVVF LOW-SLIP HOIST MOTOR DATA TOTALLY ENCLOSED

	H.P.	VOLTAGE	BTU/hr.	FRAME	F.L. RPM	F.L. AMP	WEIGHT (LBS.)
						208V / 230V / 460V	
1200 SRPM VERSION	5	208/230/460	-	215T	1150	17.3 / 15.6 / 7.8	160
	7-1/2	208/230/460	3200	254T	1175	24.1 / 21.8 / 10.9	195
	10	208/230/460	4000	256T	1176	31.6 / 28.6 / 14.3	225
	12-1/2	208/230/460	5170	284T	1160	44.2 / 40 / 20	195
	15	208/230/460	5170	284T	1160	46.4 / 42 / 21	240
	20	208/230/460	6230	286T	1160	59.7 / 54 / 27	285
	25	208/230/460	7360	324T	1170	75.2 / 68 / 34	375
	30	208/230/460	8480	326T	1170	87.4 / 79 / 39.5	410
	40	208/230/460	11610	364T	1180	103.9 / 94 / 47	485
	50	208/230/460	13920	365T	1180	130.5 / 118 / 59	515
	60	208/230/460	15700	L365T	1180	154.8 / 140 / 70	560
	75	208/230/460	18570	L365T	1180	192.4 / 174 / 87	675
900 SRPM VERSION	H.P.	VOLTAGE	BTU/hr.	FRAME	F.L. RPM	F.L. AMP 208V / 230V / 460V	WEIGHT (LBS.)
	5	208/230/460	-	254T	860	-	225
	7-1/2	208/230/460	3200	256T	860	-	200
	10	208/230/460	4000	284T	860	34.3 / 31.0 / 15.5	300
	12-1/2	208/230/460	5170	-	-	-	-
	15	208/230/460	5170	286T	860	-	320
	20	208/230/460	6230	324T	860	-	340
	25	208/230/460	7360	326T	860	-	570
	30	208/230/460	8480	364T	860	-	700
	40	208/230/460	11610	365T	860	-	880
	50	208/230/460	13920	-	-	-	-
	60	208/230/460	15700	-	-	-	-
75	208/230/460	18570	-	-	-	-	
1800 SRPM VERSION	H.P.	VOLTAGE	BTU/hr.	FRAME	F.L. RPM	F.L. AMP 208V / 230V / 460V	WEIGHT (LBS.)
	5	208/230/460	-	184T	-	-	130
	7-1/2	208/230/460	3200	213T	-	-	155
	10	208/230/460	4000	215T	-	-	160
	12-1/2	208/230/460	5170	-	-	-	-
	15	208/230/460	5170	254T	-	-	180
	20	208/230/460	6230	256T	-	-	175
	25	208/230/460	7360	284T	-	-	260
	30	208/230/460	8480	286T	-	-	340
	40	208/230/460	11610	324T	-	-	500
	50	208/230/460	13920	326T	-	-	475
	60	208/230/460	15700	364T	-	-	680
75	208/230/460	18570	365T	-	-	840	

Totally Enclosed, Non-vent motors by REULAND
 All Models have 35 foot Encoder Cables
 Standard Encoder is 2048 PPR; also available in 1024 PPR
 Constant Torque 0-60 Hz
 Variable Torque 60-90 Hz
 60 Minute Duty - Inverter Duty
 Extended End Play
 Foot Mount Motors