

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration

(Non-Mandatory Form)

Form Approved

OMB No. 1218-0072



IDENTITY (As Used on Label and List)

CPA MEDIA

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that

Section I

Manufacturer's Name

A. J. DRALLE, INC.

Emergency Telephone Number

1-815-730-0505

Address (Number, Street, City, State, and ZIP Code)

1830 W. MOUND ROAD

Telephone Number for Information

1-815-730-0505

LOLIET, IL 60436

Date Prepared

01/01/98

Signature of Preparer (optional)

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))

OSHA PEL

ACGIH TLV

Other Limits
Recommended

% (optional)

NONE KNOWN

n/a

n/a

Section III — Physical/Chemical Characteristics

Boiling Point

n/a

Specific Gravity (H₂O = 1)

1.3

Vapor Pressure (mm Hg.)

n/a

Melting Point

> 200

Vapor Density (AIR = 1)

n/a

Evaporation Rate

(Butyl Acetate = 1)

n/a

Solubility in Water

insoluble

Appearance and Odor

Fibrous solid, odorless

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used)

n/a

Flammable Limits

LEL

UEL

n/a

n/a

Extinguishing Media

Water, foam, CO₂, dry chemical

Special Fire Fighting Procedures

Fire fighting personnel should use self-contained breathing apparatus.

Usual Fire and Explosion Hazards

None

Section V — Reactivity Data

Stability	Unstable	Conditions to Avoid
	Stable X	
Open flame, sparks, high temperatures		
Incompatibility (Materials to Avoid)		
Avoid contact with strong oxidizing agents.		
Hazardous Decomposition or Byproducts		
Oxides of carbon, acetic acid.		
Hazardous Polymerization	May Occur	Conditions to Avoid
	Will Not Occur X	
None		

Section VI — Health Hazard Data

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	Inhalation	None known	None known
Health Hazards (Acute and Chronic)			
Airborne fibers may be irritating; an exposure limit of 10 mg/fiber/m ³ 8 hour TWA is recommended.			
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	No	No	No
Signs and Symptoms of Exposure			
Long-term exposure has not shown any adverse exposure symptoms.			
Medical Conditions Generally Aggravated by Exposure			
None known			
Emergency and First Aid Procedures			
None known			

Section VII — Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled
Gather material, salvage, or treat as normal refuse.
Waste Disposal Method
Dispose of material in accordance with all local, state, and federal regulations.
Precautions to Be Taken in Handling and Storing
Avoid exposure to heat, sparks, and open flame. Polyester fiber will burn.
Other Precautions

Section VIII — Control Measures

Respiratory Protection (Specify Type)			
None required under normal conditions.			
Ventilation	Local Exhaust	Special	
	Not required	Not required	
Protective Gloves	Mechanical (General)	Other	
	General mechanical vent.	n/a	
Protective Clothing or Equipment		Eye Protection	
Not required		Not required	
Work/Hygienic Practices			
Observe normal good work practices.			