

Revision Number: 003.1

Issue date: 12/10/2009

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

Odor:

LOCTITE® 7649™ PRIMER

Product type:

Accelerator

Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

IDH number:

Item number:

209715 21348

Region:

United States

Contact information:

Telephone: 860.571.5100

Emergency telephone: 860.571.5100

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Physical state: Liquid Color:

Green

Acetone

HEALTH:

FLAMMABILITY: PHYSICAL HAZARD: *2 3 0

Personal Protection:

See MSDS Section 8

DANGER:

CAUSES EYE AND SKIN IRRITATION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

FLAMMABLE LIQUID AND VAPOR

Relevant routes of exposure:

Inhalation, Skin, Eye contact, Ingestion

Potential Health Effects

Inhalation:

Vapors and mists will irritate nose and throat and possibly eyes. May cause respiratory tract

irritation. Excessive inhalation of this material causes headache, dizziness, nausea and

incoordination. Harmful by inhalation.

Skin contact:

May cause skin irritation. Solvent action can dry and defat the skin, causing the skin to crack,

leading to dermatitis.

Eve contact: Ingestion:

Vapors may irritate eyes. Contact with eyes will cause irritation.

Harmful if swallowed.

Existing conditions aggravated by

exposure:

Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Acetone	67-64-1	60 - 100
Isobutane	75-28-5	10 - 30
2-Ethylhexanoic acid	149-57-5	0.1 - 1

4. FIRST AID MEASURES

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Wash with soap and water. If symptoms develop and persist, get medical

attention.

IDH number: 209715

Product name: LOCTITE® 7649™ PRIMER

Page 1 of 5

Eye contact:

Flush with copious amounts of water, preferably, lukewarm water for at least

15 minutes, holding eyelids open all the time. Get medical attention.

Ingestion:

If conscious, drink plenty of water. Do not induce vomiting. Keep individual

calm. Get medical attention.

5. FIRE FIGHTING MEASURES

Flash point:

-20 °C (-4°F) Estimated

Autoignition temperature:

Not available

Flammable/Explosive limits - lower:

Not available

Flammable/Explosive limits - upper:

Not available

Extinguishing media:

Foam, dry chemical or carbon dioxide.

Special firefighting procedures:

Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards:

Vapors may accumulate in low or confined areas, travel considerable distance

to source of ignition, and flash back.

Hazardous combustion products:

Oxides of carbon. Oxides of nitrogen. Irritating organic vapours.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Do not allow product to enter sewer or waterways.

Clean-up methods:

Remove all sources of ignition. Ensure adequate ventilation. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder,

sawdust). Store in a partly filled, closed container until disposal.

7. HANDLING AND STORAGE

Handling:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. During use and until all vapors are gone: Keep area ventilated - do not smoke; extinguish all flames, pilot lights, and heaters; turn off stoves, electrical tools and appliances, and any other sources

of ignition.

Storage:

For safe storage, store at or below 49 °C (120.2 °F)

Store away from heat, sparks, flames, or other sources of ignition.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Acetone	500 ppm TWA 750 ppm STEL	1,000 ppm (2,400 mg/m3) TWA	None	None
Isobutane	1,000 ppm TWA	None	None	None
2-Ethylhexanoic acid	5 mg/m3 TWA Inhalable fraction and vapor.	None	None	None

IDH number: 209715

Product name: LOCTITE® 7649™ PRIMER

Engineering controls:

Use local ventilation if general ventilation is insufficient to maintain vapor

concentration below established exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure

Eye/face protection:

Safety goggles or safety glasses with side shields.

Skin protection:

Neoprene, Butyl-rubber, or nitrile-rubber gloves. Chemical resistant,

impermeable gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Color: Odor:

Odor threshold:

pH: Vapor pressure:

Boiling point/range: Melting point/ range: Specific gravity: Vapor density:

Flash point:

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper: Autoignition temperature: **Evaporation rate:**

Solubility in water: Partition coefficient (n-octanol/water):

VOC content:

Liquid

Green Acetone Not available Not available

172 mm hg (68 °F (20°C))

133 °F (56.1 °C) Not available 0.7936

-20 °C (-4°F) Estimated

Not available Not available Not available 1.9 (Ether = 1) Soluble

Not available 1.48 %; 11.7 g/I EPA Method 24

10. STABILITY AND REACTIVITY

Stability:

Stable

Hazardous reactions:

Will not occur.

Hazardous decomposition products:

Oxides of carbon. Oxides of nitrogen. Irritating organic vapours.

Incompatible materials:

Strong oxidizing agents. Acids.

Conditions to avoid:

See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10).

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Acetone	No	No	No
Isobutane	No	No	No
2-Ethylhexanoic acid	No	No	No

Hazardous components	Health Effects/Target Organs	
Acetone	Blood, Central nervous system, Irritant, Reproductive	
Isobutane	Cardiac, Central nervous system, Lung	
2-Ethylhexanoic acid	Developmental, Eyes, Irritant, Liver, Reproductive	

12. ECOLOGICAL INFORMATION

Ecological information:

Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number:

D001: Ignitable.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Hazard class or division:

Aerosols 2.1

Identification number:

UN 1950

Packing group:

None

Exceptions:

Consumer Commodity, (Not more than 1 L), ORM-D

International Air Transportation (ICAO/IATA)

Proper shipping name:

Aerosols, flammable

Hazard class or division:

2.1

Identification number:

UN 1950

Packing group:

None

Exceptions:

(Not more than 30 kg), ID8000, May Qualify as Consumer Commodity

Water Transportation (IMO/IMDG)

Proper shipping name:

AEROSOLS

Hazard class or division:

2.1 UN 1950

Identification number: Packing group:

None

Exceptions:

Limited quantity (Not more than 1 L).

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:

All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12(b) Export Notification:

None above reporting de minimus

CERCLA/SARA Section 302 EHS:

None above reporting de minimus

CERCLA/SARA Section 311/312: CERCLA/SARA 313:

Delayed Health, Fire, Immediate Health None above reporting de minimus

California Proposition 65:

This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status:

All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

WHMIS hazard class:

A, B.5, D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: Kyra Kozak Woods, Manager, Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.