


GLV-40D1

1:1 Gearless Traction Machine



COMPACT EFFICIENT VERSATILE

Ideal for Modernization
and New Construction 1:1
Double Wrap Traction (DWT)
Overhead Traction Applications



GENERAL SPECIFICATIONS

- Model: GLV-40D1
- Speed: Up to 800 fpm
- Capacity: Up to 4,000 Lbs.
- Roping: 1:1 – Double Wrap Traction
- Drive Sheave Diameter: 20" or 25"
- Maximum Sheave Shaft Load: 39,600 Lbs.
- Grooving: Up to 16 – 1/2" (20" Drive Sheave) or 14 – 5/8" (25" Drive Sheave) Ropes
- Counterweight %: 40 – 50%
- Machine Weight: 5,300 Lbs.
- Physical Dimensions: 39.82" W x 41.49" H x 47.78" D

BENEFITS

- Compact Design Inclusive of Outboard Bearing Post
- Armless Block Type Brakes – Low Audible Noise | Fewer Moving Parts
- 40 – 50% Counterweighting¹
- High-Grade Rare Earth Magnets – Highly Efficient, High Torque
- Passenger Comfort - Smooth Stepless Motor Control
- Low Force Required for Manual Brake Release

STANDARD FEATURES

- Superior 30 Pole PMAC Motor Technology
- Four Brakes – Sets of Two are Independently Controlled and Capable of Stopping and Holding 125% of Rated Capacity²
- Sheave Removal / Replacement Using Standard Field Tools
- Heidenhain ECN 1313 -2048 PPR – EnDat Digital Encoder with Standard 60 in. Pigtail Fitted with Round 17 PIN Coupling
- Thermal Protection Device
- Rope Retention – Continuous and Adjustable to Arc of Contact
- CSA listed

OPTIONS

- Machine Bases w/ Secondary and/or Deflector Sheave, and Vibratory Isolation. Loose Sheaves available.
- RopeGripper® Compatible¹
- Shielded Encoder Cable Lengths - **KEB**: 15m (49 ft), 20m (65 ft), 30m (98 ft), 40m (131 ft), 50m (164 ft) and 75m (246 ft) | **Magnatek**: 20m (65 ft), 40m (131 ft), 50m (164 ft) and 100m (328 ft)
- Rope Guards
- Breakdown | Crating | Factory Personnel Reassembly Service
- Modernization Design Services and New Construction Running Platform / Design Services
- Custom Grooving For Specific Applications

¹ Data is based on 50% counterweighting. Please contact your Hollister Whitney sales professional for lower counterweight percentages. Be sure to check www.hollisterwhitney.com/products/ regularly for product updates.




² Although a rope brake is optional, Hollister Whitney GL machines are designed to incorporate the RopeGripper® which acts directly on the suspension means mitigating the risks associated with loss of traction.

GLV-40D1 (20" WHEEL)

HW PART #	SPEED (FPM)	CAPACITY (LBS)	MOTOR RATING (HP)	POLES	RATED (RPM)	RATED VOLTAGE	RATED FREQ (HZ)	RATED CURRENT (A)	RATED TORQUE (FT-LBS)	MAXACCEL TORQUE (FT-LBS)	CWT (%)	SHEAVE DIA(")
GLV-40D1-A-V401A	400	2000	16.1	30	76	380	19	24	1118	1644	50	20
GLV-40D1-A-V402A	700	2000	28.5	30	134	380	33.5	43	1118	2236	50	20
GLV-40D1-A-V403A	800	2000	32.5	30	153	380	38.3	49	1118	2236	50	20
GLV-40D1-B-V401A	400	2500	20.4	30	76	380	19	31	1410	2818	50	20
GLV-40D1-B-V402A	700	2500	35.9	30	134	380	33.5	54	1410	2818	50	20
GLV-40D1-B-V403A	800	2500	41.0	30	153	380	38.3	61	1410	2818	50	20
GLV-40D1-C-V401A	400	3500	28.0	30	76	380	19	42	1941	3882	50	20
GLV-40D1-C-V402A	700	3500	49.4	30	134	380	33.5	74	1941	3882	50	20
GLV-40D1-C-V403A	800	3500	56.5	30	153	380	38.3	84	1941	3882	50	20
GLV-40D1-D-V401A	400	4000	31.6	30	76	380	19	47	2185	4370	50	20
GLV-40D1-D-V402A	700	4000	55.7	30	134	380	33.5	84	2185	4370	50	20
GLV-40D1-D-V403A	800	4000	63.5	30	153	380	38.3	95	2185	4370	50	20

GLV-40D1 (25" WHEEL)

HW PART #	SPEED (FPM)	CAPACITY (LBS)	MOTOR RATING (HP)	POLES	RATED (RPM)	RATED VOLTAGE	RATED FREQ (HZ)	RATED CURRENT (A)	RATED TORQUE (FT-LBS)	MAXACCEL TORQUE (FT-LBS)	CWT (%)	SHEAVE DIA(")
GLV-40D1-A-V401B	400	2000	16	30	61	380	15.3	30	1398	2796	50	25
GLV-40D1-A-V402B	700	2000	28	30	107	380	26.8	53	1398	2796	50	25
GLV-40D1-A-V403B	800	2000	32	30	122	380	30.5	60	1398	2796	50	25
GLV-40D1-B-V401B	400	2500	20.5	30	61	380	15.3	38	1764	3528	50	25
GLV-40D1-B-V402B	700	2500	35.9	30	107	380	26.8	67	1764	3528	50	25
GLV-40D1-B-V403B	800	2500	40.9	30	122	380	30.5	75.8	1764	3528	50	25
GLV-40D1-C-V401B	400	3500	28.2	30	61	380	15.3	52.0	2428	4856	50	25
GLV-40D1-C-V402B	700	3500	49.4	30	107	380	26.8	92.1	2428	4856	50	25
GLV-40D1-C-V403B	800	3500	56.3	30	122	380	30.5	104.3	2428	4856	50	25
GLV-40D1-D-V401B	400	4000	31.7	30	61	380	15.3	58.5	2731	5462	50	25
GLV-40D1-D-V402B	700	4000	55.6	30	107	380	26.8	103.6	2731	5462	50	25
GLV-40D1-D-V403B	800	4000	63.3	30	122	380	30.5	106.6	2731	5462	50	25



1 Hollister-Whitney Parkway
Quincy, IL 62305
Ph: 217.222.0466
Fax: 217.222.0493

info@hollisterwhitney.com
www.hollisterwhitney.com
sales@vantageelevation.com
www.vantageelevation.com



Chicago 877.300.5830
New York 347.226.4555
Miami 877.241.9354
L.A. 877.300.5816
Toronto 888.425.2262